

P900 AIR PURIFIER

Project name	
Architect	
Engineer	
Purchaser	
Submitted by	

Quantity		Unit(s)	Designation	PORTABLE	Model :	P900 GX
----------	--	---------	-------------	----------	---------	---------

TYPE: PORTABLE AIR PURIFIER

Standard Features

Dimensions:	
Outside dimensions (in)	3.91 (9.93 cm), 11.66 (29.61 cm), 18.66 (47.40 cm)
Air inlet/Air outlet	2.5 (49.7 cm), 7 (3.49 cm) / 3.5 (8.89 cm), 7.5 (19.05cm)
Shipping weight	11.0 lbs (5 kg)
Power	120 volt /230 v
Watts/Amps	85 Watts // .220 a (120v) .111 a (230v)
Control	Touch sensitive PAD-on/off, speed control timer
Accessories	Steel stand, carry-on handle, built in hanging hole
Air flow under load	40-75 cfm
UV lamp tye	Proprietary regular Intensity 19mm mercury vapor quartz
UV Wavelength in nanometers(nm)	254nm UVC/ 185nm UVV-one(1) inch splice
UV Lamp configuration	one (1) "J" shaped
Lenght of lamp	6.5 in (16.5 cm)
Internal Lumina coating to prevent solarization	Yes
Reflector	Anodized aluminum box/lamp parralel to airflow
Lamp change out time	17,000 hours
Lamp warranty	3 years
Ballast / motor warranty	Balast 3 years / motor 1 year
Construction	Steel/Powder coated paint
Certifications	ETL - CSA C22.2# 113 Issued- UL 507 lissued
Lamp (part number)	LMPRGXJ65
Ballast -voltage- (part number)	BST120/240GL

